

Technical data sheet

1749 sialar f



Status:	Ok
Approval:	06.01.2022

Classification	Public series
Product type:	Coated abrasives
Main industries:	Furniture Production Building Interior
Further industries:	Kitchens Panels Stone Glass Parquet Windows and Doors Marine

Product profile	
Grit type:	Silicon carbide
Grit range (total):	36-400 FEPA P / ISO 6344
Backing:	f-wt paper (FSC-certified)
Coating:	Closed
Bonding:	Resin over resin
Special coating:	
Equipment:	TopTec

Properties		Technology
Removal rate:	7 - high	- siafast - TopTec
Lifetime:	8 - long	
Finishing:	8 - good	
Flexibility:	6 - Medium	
Contact pressure:		

Advantages	
Building Interior:	<ul style="list-style-type: none">- Ideal for rotary sanding- Strong paper backing for portable machine sanding- Fast and safe change of abrasive with siafast hook and loop fastening system
Furniture Production:	<ul style="list-style-type: none">- Long life when sanding MDF boards and HDF boards and chipboard- Perfect surfaces thanks to TopTec- Dust-free process: Antistatic construction minimises dust build-up on belt, workpiece and machinery- Best surface quality- Very good finish on solid wood and veneer






Applications	
Building Interior:	<ul style="list-style-type: none"> - Keying of insulating boards - Sanding off old paint and varnish - Sanding of plaster, stone and concrete - Fine sanding of surfaces - Sanding of plaster, stone and concrete - Keying surfaces for better paint adhesion
Furniture Production:	<ul style="list-style-type: none"> - Keying of edges and surfaces on MDF board, HDF board and chipboard - Calibrating - Final sanding as preparation for painting - Final sanding on transom and high-quality veneers - Intermediate sanding of varnishes













Material		
Building Interior:	<ul style="list-style-type: none"> Concrete Dry wall lining boards Lacquers Lacquers Lacquers Mineral materials Old lacquer Old paint Plaster Primer filler Wood Wood Wood Wood-based materials 	<ul style="list-style-type: none"> <input type="radio"/> Plastics <input type="radio"/> Stone <input type="radio"/> Plastics <input type="radio"/> Concrete <input checked="" type="radio"/> Dry wall lining boards <input type="radio"/> PU lacquer <input type="radio"/> Polyester lacquer <input type="radio"/> UV lacquer <input checked="" type="radio"/> Mineral fibreboard <input checked="" type="radio"/> Old lacquer <input checked="" type="radio"/> Old paint <input checked="" type="radio"/> Plaster <input type="radio"/> Primer filler <input checked="" type="radio"/> Soft wood <input checked="" type="radio"/> Hard wood <input type="radio"/> Hard wood <input checked="" type="radio"/> MDF board
Furniture Production:	<ul style="list-style-type: none"> Coatings Coatings Coatings Coatings Coatings Minerals Plastics Solid wood Solid wood Wood-based materials Wood-based materials Wood-based materials 	<ul style="list-style-type: none"> <input checked="" type="radio"/> Bodyfiller <input checked="" type="radio"/> Primer filler <input checked="" type="radio"/> PU lacquer <input checked="" type="radio"/> Polyester lacquer <input checked="" type="radio"/> UV lacquer <input type="radio"/> Stone <input type="radio"/> Plastics <input checked="" type="radio"/> Soft wood <input type="radio"/> Hard wood <input checked="" type="radio"/> Chipboard <input checked="" type="radio"/> MDF board <input type="radio"/> Mineral fibreboard

Technical data sheet

1749 sialar f



Conversion forms	Upper conversion	Lower conversion
	Rolls	<ul style="list-style-type: none"> - Jumbolino - Jumbo rolls - Paper rolls
	Strips	<ul style="list-style-type: none"> - siafast strips - Various strips
	Delta and polygons	<ul style="list-style-type: none"> - Delta and polygons
	Discs	<ul style="list-style-type: none"> - Double-sided discs - siafast discs - Self-adhesive discs - Various discs
	Belts	<ul style="list-style-type: none"> - Wide belts (width: from 400 mm) - Hand sanding belts and sleeves (width: 30–390 mm/length: up to 950 mm) - Narrow, edge and long belts (width: 25–399 mm/length: up to 10,700 mm)

Application	Superordinate group	Subgroup
	Portable machine sanding	random orbital sander
	Portable machine sanding	Angle grinder
	Portable machine sanding	Orbital sanders
	Portable machine sanding	Delta sander
	Manual sanding	Hand sanding with sanding block
	Stationary belt sanding	Edge belt sanding
	Stationary belt sanding	Pad wide belt sanding
	Stationary belt sanding	Cross belt sanding
	Stationary belt sanding	Contact wide belt sanding
	Stationary belt sanding	Combined wide belt sanding
	Stationary belt sanding	Long belt sanding
	Stationary machine sanding	Stationary disc sanding
Cut:		

Technical data sheet

1749 siaral f



Details	
No suitability for:	<ul style="list-style-type: none"> - In coarse grit range on coniferous wood - Calibrating and flattening of wood with a high oil and resin content - Wet sanding - Greasy materials
Sanding recommendation:	- P80 - P400: use belts wider than 1800 mm only after preliminary tests
Safety recommendation:	<p>Observe the current valid safety recommendations at: www.sia-abrasives.com > Expertise > Safety</p> <ul style="list-style-type: none"> - Pay attention to the abrasives safety data sheet (available from sia Abrasives) - Follow the general FEPA safety recommendations - Use eye and face protection - Use an effective dust extraction unit or wear a fine dust mask

Communication			
Claim:	The number 1 for sanding of MDF, HDF and chipboard		
Copy:	A specialist abrasive for keying MDF, HDF and chipboard, 1749 siaral f not only has a long lifetime, it also produces a high-quality surface finish.		
Image material:	Product Top View (PTV)	Front side: ID	Rear side: ID
	Application image	Building Interior: ID 4532	Furniture ID 5616
	Product show:		
	Macro shot:		
	Packaging image:		
	Product group image:		ID 7593

- Main application
- Secondary application